



The ideal means of transportation of difficult, heavy and bulky loads

Safe - an electromagnet brake supports the operator

Economical - designed for a one - two man operation

Easy to maneuver - thanks to a compact style and build in hub driving system

Easy to handle - all control switches are on the control panel

Easy direction controlling as well as during climbing up- and downstairs.



Non-standard performances are standard for us



Design

independent moving crawlers, motor 2x600 W; battery 2 x 12 V / 65 Ah; capacity 50 floors; charger 230 V / 50 Hz / 15 A; colour: blue RAL 5017.

Standard Type:

with horizontal loading platform with a new traction system based on independent tracks allowing to turn both on flat grounds, on the stairs and in narrow space.

Typ Horizontal:

same as above standard type with an additional feature, horizontal lifting platform (load remains in a horizontal position when transporting).

Typ Vertikal:

same as standard type but equipped additionally with a 90° vertical turning platform (objects can be loaded directly from the ground).



	Typ	Standard	Horizontal	Vertikal
	Artikel-Nr.	330.025	330.026	330.027
loading capacity	kg	600	600	600
length	mm	min. 1280	min. 1280	1280 - 1680
usable length	mm	min. 1360	min. 1360	min. 1360
width	mm	540	540	540
measurements of loading platform	mm	1205 x 430	1205 x 430	1205 - 1605 x 430
front extension	mm	500	500	500
height of platform	mm	325 - 700	370 - 700	405 - 700
speed	m/min.	12,0	12,0	12,0
pressure	bar	110	125	130
dead weight	kg	275	315	320

